



Vibroisolation Pads VIBRASTOL

| Product | VIBRASTOL 40 | VIBRASTOL 75 | VIBRASTOL 110 | VIBRASTOL 155 | VIBRASTOL 155S | VIBRASTOL 200 | VIBRASTOL 200S | VIBRASTOL 200F |
|---|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Maximum static load ¹⁾ | 20 kg | 200 kg | 300 kg | 800 kg | 1000 kg | 1400 kg | 3000 kg | 4000 kg |
| Maximum load for dynamic working Machines ²⁾ | 10 kg | 100 kg | 150 kg | 600 kg | 750 kg | 1000 kg | 1800 kg | 2800 kg |
| Maximum load for impact working Machines ³⁾ | - | - | - | 400 kg | 600 kg | 800 kg | 1600 kg | 2200 kg |
| Cover's material | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium |
| Elastomer hardness | 57 (+/-3) Sh A | 57 (+/-3) Sh A | 57 (+/-3) Sh A | 57 (+/-3) Sh A | 70 (+/-3) Sh A | 57 (+/-3) Sh A | 70 (+/-3) Sh A | 80 (+/-3) Sh A |
| Elastomer color | red | red | red | red | red | red | red | red |
| Nominal diameter D | 34 | 67 | 103 | 144 | 144 | 187 | 187 | 187 |
| Maximum diameter D max | 39 | 75 | 111 | 158 | 158 | 202 | 202 | 202 |
| Total height B | 51 | 82 | 102 | 150 | 150 | 185 | 185 | 185 |
| Pad height A | 14 | 21 | 27 | 45 | 45 | 60 | 60 | 60 |
| Adjustable height H min | 24 | 30 | 40 | 50 | 50 | 70 | 70 | 70 |
| Adjustable height H max | 45 | 57 | 76 | 55 | 55 | 80 | 80 | 80 |
| Adjusting-leveling screw | M8x40 | M8x60 | M10x60 | M12x120 | M16x140 | M16x140 | M20x180 | M20x180 |

1) Control and measuring apparatus, scales, cisterns, etc.

2) Milling machines, turning lathes, grinding machines, compressors, extrusion machines, presses, etc.


3) Injection moulding machines, blanking presses, printing machines, etc.

Stolan[®]

ELASTOMER



VIBRASTOL 40 – 110



VIBRASTOL 155 – 200

